





# NTN Bearing Manufacturing



## 12 mm x 24 mm x 6 mm SKF 71901 CE/HCP4AH angular contact ball bearings

Bearing No. 71901 CE/HCP4AH

71901 CE/HCP4AH Bearing 2D drawings and 3D CAD models

Size	24x12x6 mm
Bore Diameter	12 mm
Outer Diameter	24 mm
Width	6 mm
d	12 mm
D	24 mm
B	6 mm
d <sub>1</sub>	16 mm
d <sub>2</sub>	15.26 mm
D <sub>1</sub>	19.95 mm
K	0.5 mm
C <sub>1</sub>	3.65 mm
r <sub>1,2</sub> - min.	0.3 mm
r <sub>3,4</sub> - min.	0.15 mm
a	5.7 mm
d <sub>a</sub> - min.	14 mm
d <sub>b</sub> - min.	14 mm
D <sub>a</sub> - max.	22 mm
D <sub>b</sub> - max.	23.2 mm
r <sub>a</sub> - max.	0.3 mm
r <sub>b</sub> - max.	0.15 mm
d <sub>n</sub>	16.8 mm
Basic dynamic load rating - C	2.1 kN
Basic static load rating - C <sub>0</sub>	0.915 kN



## NTN Bearing Manufacturing

Fatigue load limit - $P_u$	0.039 kN
Limiting speed for grease lubrication	109000 r/min
Limiting speed for oil lubrication	165000 mm/min
Ball - $D_w$	3.175 mm
Ball - $z$	12
$G_{ref}$	0.1 cm <sup>3</sup>
Calculation factor - $f_0$	7.8
Preload class A - $G_A$	11 N
Preload class B - $G_B$	34 N
Preload class C - $G_C$	68 N
Calculation factor - $f$	1.04
Calculation factor - $f$	1
Calculation factor - $f_{2A}$	1
Calculation factor - $f_{2B}$	1.05
Calculation factor - $f_{2C}$	1.09
Calculation factor - $f_{HC}$	1.01
Preload class A	12 N/micron
Preload class B	19 N/micron
Preload class C	26 N/micron
$d_1$	16 mm
$d_2$	15.26 mm
$D_1$	19.95 mm
$C_1$	3.65 mm
$r_{1,2}$ min.	0.3 mm
$r_{3,4}$ min.	0.15 mm
$d_a$ min.	14 mm
$d_b$ min.	14 mm
$D_a$ max.	22 mm
$D_b$ max.	23.2 mm



## NTN Bearing Manufacturing

$r_a$ max.	0.3 mm
$r_b$ max.	0.15 mm
$d_n$	16.8 mm
Basic dynamic load rating C	2.12 kN
Basic static load rating $C_0$	0.915 kN
Fatigue load limit $P_u$	0.039 kN
Attainable speed for grease lubrication	109000 r/min
Attainable speed for oil-air lubrication	165000 r/min
Ball diameter $D_w$	3.175 mm
Number of balls z	12
Reference grease quantity $G_{ref}$	0.1 cm <sup>3</sup>
Preload class A $G_A$	11 N
Static axial stiffness, preload class A	12 N/ $\mu$ m
Preload class B $G_B$	34 N
Static axial stiffness, preload class B	19 N/ $\mu$ m
Preload class C $G_C$	68 N
Static axial stiffness, preload class C	26 N/ $\mu$ m
Calculation factor f	1.04
Calculation factor $f_1$	1
Calculation factor $f_{2A}$	1
Calculation factor $f_{2B}$	1.05
Calculation factor $f_{2C}$	1.09
Calculation factor $f_{HC}$	1.01
Calculation factor $f_0$	7.8
Mass bearing	0.009 kg